

| <b>Plum Creek AB Marine Grade Plywood</b> |  |
|---|--|
| <b>SPECS</b>                              | <ul style="list-style-type: none"> <li>• Slow growth inland Douglas Fir and Western Larch yield fine-grained, smooth faces</li> <li>• All Group 1, Struc 1 Species</li> </ul>  |
| <b>FACES</b>                              | <ul style="list-style-type: none"> <li>• "A" grade faces shall be limited to a total of nine repairs in a 4' x 8' panel.</li> </ul>  |
| <b>BACKS, CENTERS &amp; CORES</b>         | <ul style="list-style-type: none"> <li>• All backs, centers and inner plies shall be "B" grade or better and shall be full length and full width.</li> <li>• Neither edge of a panel shall have any cross band gap or edge splits in excess of 1/8" wide or 4 in number. No inner ply laps are allowed.</li> </ul>   |
| <b>CONSTRUCTION &amp; THICKNESS</b>       | <p><b>Thickness Ply count</b></p> <p>1/4"     3 Ply</p> <p>3/8"     4 Ply</p> <p>1/2"     5 Ply</p> <p>5/8"     7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Panel thickness to 1 1/2"</li> <li>• Solid long length to 102"</li> <li>• Scarfed lengths to 16'</li> <li>• Full thick</li> <li>• Tongue and groove available on 5/8" - 1 1/8"</li> </ul> |

| <b>Plum Creek AC Sanded Plywood</b> |   |
|-------------------------------------|---|
| <b>SPECS</b>                        | <ul style="list-style-type: none"> <li>• Slow growth inland Douglas Fir and Larch yield fine-grained, smooth faces</li> <li>• All Group 1, Struc 1 Species</li> </ul>   |
| <b>FACES</b>                        | <ul style="list-style-type: none"> <li>• "A" grade veneer</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• 15 plug average assures the highest face quality</li> <li>• Fully sanded face</li> </ul>   |
| <b>BACKS, CENTERS &amp; CORES</b>   | <ul style="list-style-type: none"> <li>• Plum Creek's High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece "C" grade or better center and back</li> </ul>   |
| <b>CONSTRUCTION &amp; THICKNESS</b> | <p><b>Thickness Ply count</b></p> <p>1/4"     3 Ply</p> <p>3/8"     4 Ply</p> <p>1/2"     5 Ply</p> <p>5/8"     5 or 7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4' x 8'</li> <li>• Panel thickness to 1 1/2"</li> <li>• Solid long length to 102"</li> <li>• Scarfed panels to 16'</li> <li>• Tongue and groove available on 5/8" - 1 1/8"</li> <li>• Underlayment stamp available</li> </ul> |

| <b>Plum Creek BC Sanded Plywood</b> |   |
|-------------------------------------|---|
| <b>SPECS</b>                        | <ul style="list-style-type: none"> <li>• Slow growth inland Douglas Fir and Larch yield fine-grained faces</li> <li>• All Group 1, Struc 1 Species</li> </ul>   |
| <b>FACES</b>                        | <ul style="list-style-type: none"> <li>• Premium "B" grade veneer</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Unlimited plugs and repairs</li> <li>• Fully sanded face with 60 grit paper</li> </ul>   |
| <b>BACKS, CENTERS &amp; CORES</b>   | <ul style="list-style-type: none"> <li>• Plum Creek's High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece "C" grade or better center and back</li> </ul>   |
| <b>CONSTRUCTION &amp; THICKNESS</b> | <p><b>Thickness Ply count</b></p> <p>1/4"     3 Ply</p> <p>3/8"     4 Ply</p> <p>1/2"     5 Ply</p> <p>5/8"     5 or 7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4' x 8'</li> <li>• Panel thickness to 1 1/2"</li> <li>• Solid long length to 102"</li> <li>• Scarfed panels to 16'</li> <li>• Tongue and groove available on 5/8" - 1 1/8"</li> </ul> |

| <b>Plum Creek Douglas Fir Siding</b> |  |
|--------------------------------------|--|
| <b>SPECS</b>                         | <ul style="list-style-type: none"> <li>• Inland western Douglas Fir known for its slow growth, fine texture and tight grain</li> <li>• All Group 1, Struc 1 Species</li> <li>• Finishing characteristics well-suited for paint, heavy body or semi-transparent stain</li> <li>• High ply count construction ensures superior strength and stability</li> </ul> |
| <b>FACES</b>                         | <ul style="list-style-type: none"> <li>• APA "A" grade face</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Average 14 plugs per panel</li> </ul>   |
| <b>BACKS, CENTERS &amp; CORES</b>    | <ul style="list-style-type: none"> <li>• Plum Creek's High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece "C" grade center and back</li> </ul>  |
| <b>CONSTRUCTION &amp; THICKNESS</b>  | <p><b>Thickness Ply count</b></p> <p>3/8"      4 Ply No Groove</p> <p>1/2"      5 Ply No Groove, 4" OC, 8" OC</p> <p>5/8"      5 Ply No Groove, 4" OC, 8" OC</p> <ul style="list-style-type: none"> <li>• Scarfed 9' and 10' available</li> <li>• Rough texture or scratch sand</li> <li>• Ship lap or square edge</li> </ul>                                  |

| <b>Plum Creek MarineDeck™</b>       |   |
|-------------------------------------|---|
| <b>SPECS</b>                        | <ul style="list-style-type: none"> <li>• Designed for rigorous marine use with superior “CP” grade face</li> <li>• All Group 1, Struc 1 Species</li> <li>• Available with solid core under the face</li> <li>• 2 side panels available</li> </ul>   |
| <b>FACES</b>                        | <ul style="list-style-type: none"> <li>• “C” plugged grade veneer</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Splits over 1/16” are filled. Sound, tight knots up to 1 1/2"</li> <li>• Face is touch sanded with 60 grit paper</li> </ul>  |
| <b>BACKS, CENTERS &amp; CORES</b>   | <ul style="list-style-type: none"> <li>• Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece “C” grade or better center and back</li> </ul>   |
| <b>CONSTRUCTION &amp; THICKNESS</b> | <p><b>Thickness Ply count</b></p> <p>1/4"     3 Ply</p> <p>3/8"     4 Ply</p> <p>1/2"     5 Ply</p> <p>5/8"     5 or 7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4’ x 8’</li> <li>• Panel thickness to 1 1/2"</li> <li>• Solid long length to 102"</li> <li>• Scarfed length to 16'</li> <li>• Tongue and groove available on 5/8" - 1 1/8"</li> <li>• Underlayment stamp available</li> </ul> |

| <b>Plum Creek MarineTech™</b>       |   |
|-------------------------------------|---|
| <b>SPECS</b>                        | <ul style="list-style-type: none"> <li>• Designed for rigorous marine use with superior “B” grade faces</li> <li>• All Group 1, Struc 1 Species</li> <li>• Available with solid core under the face</li> <li>• 2 side panels available</li> </ul>   |
| <b>FACES</b>                        | <ul style="list-style-type: none"> <li>• “B” and better face grade with no open holes or defects</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Splits over 1/32” are filled. Only sound, tight pin knots allowed</li> <li>• Face is fully sanded with 60 grit paper</li> </ul>   |
| <b>BACKS, CENTERS &amp; CORES</b>   | <ul style="list-style-type: none"> <li>• Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One side panel has a high “C” grade back chosen for minimal knot holes and splits</li> <li>• Two side panel has a “B” plugged back – no open knot holes or defects</li> <li>• Back is touch sanded with 60 grit paper</li> <li>• One piece high “C” center and back</li> </ul> |
| <b>CONSTRUCTION &amp; THICKNESS</b> | <p><b>Thickness Ply count</b></p> <p>1/4"     3 Ply</p> <p>3/8"     4 Ply</p> <p>1/2"     5 Ply</p> <p>5/8"     5 or 7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 48” x 96”</li> <li>• Panel thickness to 1 1/2"</li> <li>• Solid long length to 102"</li> <li>• Scarfed lengths to 16'</li> <li>• Tongue and groove available on 5/8" - 1 1/8"</li> </ul>  |

| <b>Plum Creek MDO Sign Grade</b>    |  |
|-------------------------------------|--|
| <b>SPECS</b>                        | <ul style="list-style-type: none"> <li>• A quality Medium Density Overlay plywood product</li> <li>• All Group 1, Struc 1 Species</li> <li>• One or two-step process</li> </ul>  |
| <b>FACES</b>                        | <ul style="list-style-type: none"> <li>• "B" grade veneer under paper</li> <li>• Wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Pre-primed paper available</li> <li>• One or two side panel available in one or two step process</li> <li>• Fully sanded face with two step process</li> </ul>              |
| <b>BACKS, CENTERS &amp; CORES</b>   | <ul style="list-style-type: none"> <li>• Plum Creek's High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece "C" grade or better center and back</li> <li>• Primed one side panels produced with a backer sheet</li> </ul> |
| <b>CONSTRUCTION &amp; THICKNESS</b> | <p><b>Thickness Ply count</b></p> <p>3/8"      4 Ply</p> <p>1/2"      5 Ply</p> <p>5/8"      5 or 7 Ply</p> <p>3/4"      7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4' x 8'</li> <li>• Scarfed panels to 10'</li> </ul>  |

| <b>Plum Creek Ultra-Pour™ BBO &amp; ES Concrete Form</b> |  |
|--|--|
| <b>SPECS</b>   | <ul style="list-style-type: none"> <li>• Standard and premium grade available</li> <li>• All Group 1, Struc 1 Species</li> <li>• Nox-Crete™ release agent</li> <li>• Highest quality edge seal</li> </ul>  |
| <b>STANDARD GRADE</b>                                    | <ul style="list-style-type: none"> <li>• APA “B” grade Douglas Fir face and back</li> <li>• Face and back touch-sanded with 60 grit paper</li> </ul>   |
| <b>PREMIUM GRADE</b>                                     | <ul style="list-style-type: none"> <li>• Superior “B” grade Douglas Fir face and back</li> <li>• Fully repaired panel</li> <li>• Face and back fully sanded with 60 grit paper</li> </ul>  |
| <b>CENTERS &amp; CORES</b>                               | <ul style="list-style-type: none"> <li>• Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece “C” grade center</li> </ul> |
| <b>CONSTRUCTION &amp; THICKNESS</b>                      | <p><b>Thickness Ply count</b></p> <p>5/8"      7 Ply</p> <p>3/4"      7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4’ x 8’</li> <li>• 2’ x 8’ size available</li> <li>• Full thickness</li> <li>• Oil and edge sealed</li> </ul> |

| <b>Plum Creek Ultra-Pour™ HDO Concrete Form</b> |  |
|---|--|
| <b>SPECS</b>                                    | <ul style="list-style-type: none"> <li>• Two-Step process</li> <li>• All Group 1, Struc 1 Species</li> <li>• Highest quality edge seal</li> </ul>  |
| <b>FACES</b>                                    | <ul style="list-style-type: none"> <li>• APA “B” grade face</li> <li>• Smooth uniform finish enhances durability of product</li> <li>• Increased pours</li> <li>• Minimum grain transfer</li> </ul>  |
| <b>BACKS, CENTERS &amp; CORES</b>               | <ul style="list-style-type: none"> <li>• Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece “C” grade center and back</li> </ul>  |
| <b>CONSTRUCTION &amp; THICKNESS</b>             | <p><b>Thickness Ply count</b></p> <p>1/2"      5 Ply 100/30 100/100 120/30 120/120</p> <p>5/8"      7 Ply 100/30 100/100 120/30 120/120</p> <p>3/4"      7 Ply 100/30 100/100 120/30 120/120</p> <ul style="list-style-type: none"> <li>• Standard size 4’ x 8’</li> <li>• 2’ x 8’ size available</li> <li>• Full thick</li> </ul> |

## Plum Creek Ultra-Pour™ MDO Concrete Form

|                                     |   |
|-------------------------------------|---|
| <b>SPECS</b>                        | <ul style="list-style-type: none"> <li>• One and Two-Step process available</li> <li>• All Group 1, Struc 1 Species</li> <li>• Nox-Crete™ release agent</li> <li>• Highest quality edge seal</li> </ul>   |
| <b>ONE-STEP PROCESS</b>             | <ul style="list-style-type: none"> <li>• APA “B” grade face</li> <li>• Paper and veneer are pressed together in a one-step process</li> <li>• Minimum grain transfer</li> <li>• Matte finish</li> </ul>   |
| <b>TWO-STEP PROCESS</b>             | <ul style="list-style-type: none"> <li>• APA “B” grade face</li> <li>• Paper is pressed to sanded blank in a secondary process</li> <li>• 2 side panels available</li> <li>• Minimum grain transfer</li> <li>• Matte finish</li> </ul>  |
| <b>CENTERS &amp; CORES</b>          | <ul style="list-style-type: none"> <li>• Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece “C” grade center and back</li> </ul>                       |
| <b>CONSTRUCTION &amp; THICKNESS</b> | <p><b>Thickness Ply count</b></p> <p>1/2"     5 Ply</p> <p>5/8"     5 or 7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4’ x 8’</li> <li>• 2’ x 8’ size available</li> <li>• Full thickness</li> <li>• One or two side available</li> </ul> |